

**Filterelement**  
*Filter element*

0660D0100N

**Material-Nr.:***Material no.:***Bezeichnung:**

9.660LA PWR10-A00-0-M SO3000

*Designation:***Filterfeinheit<sup>1</sup>:**

10 µm

*Filtration grade<sup>1</sup>:***Filtrationsquotient<sup>1</sup>:** $\beta_{10}(c) = 200 / \beta_{11}(c) = 1000$  (ISO 16889)*Filtration ratio<sup>1</sup>:***Filtermaterial<sup>1</sup>:**

Mehrlagiges Glasfasermaterial

*Filter media<sup>1</sup>:*

Multilayer glass fiber material

**Kollapsdruckbeständigkeit bar [psi]:**

30 [435]

*Collapse pressure rating bar [psi]:***Temperaturbeständigkeit °C [°F]:**


-40...100 [-40...212]

*Temperature rating °C [°F]:***Bypass Öffnungsdruck bar [psi]:**

/

*Bypass cracking pressure bar [psi]:***Dichtungswerkstoff:**

NBR

*Sealing material:***Abmessungen mm [inch]:***Dimensions mm [inch]:***OD** = 90,5 [3.6]**ID** = 48,1 [1.9]**L** = 329,0 [12.9]**Gewicht kg [lbs]:** 1,3 [2.9]*Weight kg [lbs]:*
 Vereinfachte Darstellung  
 The drawing shown is a simplistic representation