







LABEL (铭牌):




WIRING DIAGRAM (接线图):



FLOW RATE CURVE (风量曲线):



UNIT 类型	Axial fan motor 外转子轴流风机
MOTOR 电机型式	Single phase motor with capacitor
MOTOR TYPE 电机型号	YWF2E-200S-92/15-GB
VOLTAGE 额定电压 (V)	220
FREQUENCY 频率 (Hz)	50/60
INPUT POWER 输入功率 (W)	55/65
CURRENT 电流 (A)	0.25/0.28
SPEED 转速 (r/min)	2500/2700
AIR FLOW 20Pa 风量 (m³/h)	716/845
NOISE 噪音 (dBA)	52/54
CAPACITOR 电容 (μ F/450V)	2
ROTATION 旋转方向	CCW ,looking into the end-shield 逆时针, 从端盖端方向看
INSULATION CLASS 绝缘等级	F
MOTOR PROTECTION 电机保护	Thermocontact 150±5℃ 热保护器
TEMPERATURE RISE 温升	75K max 运行温升不超过75K
TYPE OF PROTECTION 防护等级	IP54
OPERATING TYPE 工作定额	S1 连续工作制
AMBIENT TEMPERATURE 适用环境温度	-30℃ +60℃
BEARINGS 轴承型式	Ball bearings 滚珠轴承
MOUNTING TYPE 安装方式	Square Frame 工频方框
ELECTRICAL CONNECTION 电源线	Lead wire 4G 0.50mm² ,Length 220mm 单芯0.22米(外露) 四芯线, 不用护套线
APPROVALS 认证标记	CE
NET WEIGHT/GROSS WEIGHT 净重/毛重	2.5/3.0kg
PACKING 包装	24.5*24.5*10cm

REV.	DESCRIPTION	APPROVED	DATE	DRN. BY	SIGN	DATE	TITLE
				CHD. BY			YWF2E-200S-92/15-GB
				ENG. BY			PROJECTION 
				APP. BY			A4 SCALE SHEET: of