

**Silicon PNP Power Transistors**

**2SA957 2SA958**

**DESCRIPTION**


- With TO-220 package
- High breakdown voltage
- High power dissipation

**APPLICATIONS**

- For general purpose applications

**PINNING**

PIN	DESCRIPTION
1	Emitter
2	Collector;connected to mounting base
3	Base



**Absolute maximum ratings(Ta=25°C)**

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V <sub>CBO</sub>	Collector-base voltage	2SA957	-150	V
		2SA958	-200	
V <sub>CEO</sub>	Collector-emitter voltage	2SA957	-150	V
		2SA958	-200	
V <sub>EBO</sub>	Emitter-base voltage	Open collector	-6	V
I <sub>C</sub>	Collector current		-2.0	A
I <sub>B</sub>	Base current		-1.0	A
P <sub>T</sub>	Total power dissipation	T <sub>C</sub> =25°C	30	W
T <sub>j</sub>	Junction temperature		150	°C
T <sub>stg</sub>	Storage temperature		-55~150	°C

## Silicon PNP Power Transistors

## 2SA957 2SA958

## CHARACTERISTICS

T<sub>j</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT	
V <sub>CEO(BR)</sub>	Collector-emitter breakdown voltage	2SA957	I <sub>C</sub> =-25mA, I <sub>B</sub> =0	-150			V
		2SA958		-200			
V <sub>CEsat</sub>	Collector-emitter saturation voltage	I <sub>C</sub> =-0.7A; I <sub>B</sub> =-0.07A			-1.5	V	
I <sub>CBO</sub>	Collector cut-off current	2SA957			-100	μ A	
		2SA958					V <sub>CB</sub> =-200V; I <sub>E</sub> =0
I <sub>EBO</sub>	Emitter cut-off current	V <sub>EB</sub> =-6V; I <sub>C</sub> =0			-1.0	mA	
h <sub>FE</sub>	DC current gain	I <sub>C</sub> =-0.7A; V <sub>CE</sub> =-10V	40				
f <sub>T</sub>	Transition frequency	I <sub>C</sub> =-0.2A; V <sub>CE</sub> =-12V		20		MHz	

Switching times resistive load

t <sub>r</sub>	Rise time	I <sub>C</sub> =-1.0A I <sub>B1</sub> =- I <sub>B2</sub> =-0.1A R <sub>L</sub> =20 Ω ;V <sub>CC</sub> =-20V		0.4		μ s
t <sub>s</sub>	Storage time			1.5		μ s
t <sub>f</sub>	Fall time			0.5		μ s

Silicon PNP Power Transistors

2SA957 2SA958

PACKAGE OUTLINE




Fig.2 Outline dimensions(unindicated tolerance:  $\pm 0.10$  mm)