SELF-CONTAINED ESCAP EXIT LIGHTS WITH SUPER CAPACITOR

| Supply voltage 220-240 V AC | Aalto = Aalto Control compatible (incl. Lumi Test) | M = Self-contained luminaire with Lumi Test self-testing | Escap = Self-contained luminaire with 1 h Super capacitor backup

SUPPLY		Product family	IP class	Product code	Light source	Operation mode	Product catalogue page
VOLTAGE: 220-240 V AC	13 V	ESC 81	IP44	TWS8192WA	LED	1 h Escap + Aalto	82
				TWS8192WM	LED	1 h Escap + M	82
		ESC 80	IP44	TWS8092WA	LED	1 h Escap + Aalto	75
	S 🔶			TWS8092WM	LED	1 h Escap + M	75
		ESC 90	IP44	TWS9092WA	LED	1 h Escap + Aalto	67
				TWS9092WM	LED	1 h Escap + M	67
				TWS8592W	LED	1 h Escap	88
		ESC 10	IP20	TWS8592WA	LED	1 h Escap + Aalto	88
	5 V			TWS8592WM	LED	1 h Escap + M	88
		Silver	IP20	TWS6592WA	LED	1 h Escap + Aalto	102
	5 +			TWS6592WM	LED	1 h Escap + M	102
		Silver	IP20	TWS6692WA	LED	1 h Escap + Aalto	106
	E V			TWS6692WM	LED	1 h Escap + M	106
		Silver	IP20	TWS6792WA	LED	1 h Escap + Aalto	110
	15 V			TWS6792WM	LED	1 h Escap + M	110
	R	Silver	IP20	TWS6892WA	LED	1 h Escap + Aalto	114
	15 V			TWS6892WM	LED	1 h Escap + M	114
		ESC 6 L	IP44	TWS6292WA	LED	1 h Escap + Aalto	118
	54			TWS6292WM	LED	1 h Escap + M	118
		ESC 4	IP44	TWS1792W	LED	1 h Escap	122
	SV			TWS1792WA	LED	1 h Escap + Aalto	122
				TWS1792WM	LED	1 h Escap + M	122
	173 J	Solid Exit	IP65	TWS3092WA	LED	1 h Escap + Aalto	140
		Cond Lan		TWS3092WM	LED	1 h Escap + M	140

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR

| Supply voltage 220-240 V AC | Aalto = Aalto Control compatible (incl. Lumi Test) | M = Self-contained luminaire with Lumi Test self-testing | Escap = Self-contained luminaire with 1 h Super capacitor backup

SUPPLY	Product family	IP class	Product code	Light source	Operation mode	Product catalogue page
VOLTAGE:	Linespot (recess mounting)	IP20	TWS5092WA	LED	1 h Escap + Aalto	172
220-240 V			TWS5092WM	LED	1 h Escap + M	172
AC	Linespot II Lowbay	IP44	TWS9992WA	LED	1 h Escap + Aalto	154
(1)	(surface mounting)		TWS9992WM	LED	1 h Escap + M	154
	Linespot II Midbay (surface mounting)	IP44	TWS8892WA	LED	1 h Escap + Aalto	160
Sec			TWS8892WM	LED	1 h Escap + M	160
	Zonespot II Lowbay (surface mounting)	IP44	TWS9292WA	LED	1 h Escap + Aalto	178
			TWS9292WAC	LED	1 h Escap + Aalto	178
			TWS9292WM	LED	1 h Escap + M	178
			TWS9292WMC	LED	1 h Escap + M	178
	Zonespot II Midbay (surface mounting)	IP44	TWS9392WA	LED	1 h Escap + Aalto	184
			TWS9392WAC	LED	1 h Escap + Aalto	184
			TWS9392WM	LED	1 h Escap + M	184
			TWS9392WMC	LED	1 h Escap + M	184
	Zonespot II Lowbay (recess mounting)	IP20/ IP44	TWS0492WA	LED	1 h Escap + Aalto	192
			TWS0492WAC	LED	1 h Escap + Aalto	192
			TWS0492WM	LED	1 h Escap + M	192
			TWS0492WMC	LED	1 h Escap + M	192
	Linespot II Lowbay (recess mounting)	IP20/ IP44	TWS1492WA	LED	1 h Escap + Aalto	166
			TWS1492WM	LED	1 h Escap + M	166
	Slimspot (recess mounting)	IP20	TWS9792WA	LED	1 h Escap + Aalto	230
			TWS9792WM	LED	1 h Escap + M	230
	Solid Line/ Zone Lowbay (surface mounting)	IP65	TWS3292WA	LED	1 h Escap + Aalto	198
×			TWS3292WM	LED	1 h Escap + M	198
			TWS4292WA	LED	1 h Escap + Aalto	204
			TWS4292WM	LED	1 h Escap + M	204
	Solid Line/ Zone Midbay (surface mounting)	IP65	TWS3692WA	LED	1 h Escap + Aalto	210
1 4004000 1			TWS3692WM	LED	1 h Escap + M	210
×			TWS4392WA	LED	1 h Escap + Aalto	216
			TWS4392WM	LED	1 h Escap + M	216