

# 75W Single Output DIN Rail Power



- Universal AC input / Full range
- UL508 listed
- Installed on DIN rail TS35 / 7.5 or 15
- Protections: Short circuit / Overload / Over voltage / Over temp.
- Fixed switching frequency at 50KHz
- Approvals: UL / CUL / TUV / CB / CE
- LED indicator for power on
- Cooling by free air convection
- 100% full load burn-in test
- 3 years warranty

AC input voltage range	85~264VAC; 120~370VDC
AC inrush current	Cold start, 20A at 115VAC, 40A at 230VAC
DC adjustment range	12V: 12~14V, 24V: 24~28V, 48V: 48~53V
Overload protection	105%~150% constant current limiting, auto-recovery
Over voltage protection	121%~142% rated output voltage
Setup, rise, hold up time	1000ms, 60ms, 60ms at full load and 230VAC
Withstand voltage	I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1minute
Working temperature	-10~60°C (refer to output derating curve)
Safety standards	UL508, TUV EN60950-1 approved
EMC standards	EN55022 class B, EN61000-3-2,3, EN61000-6-2, EN61000-4-2,3,4,5,6,8,11, ENV50204
Connection	I/P: 3 poles, O/P: 4 poles screw DIN terminal
Packing	0.6kg ; 20pcs / 13.0kg / 1.1CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
10531	DR-75-12	12V, 0~6.3A	±2%	100mV	76%
10532	DR-75-24	24V, 0~3.2A	±1%	150mV	80%
10533	DR-75-48	48V, 0~1.6A	±1%	240mV	81%