

# NGD8201N, NGD8201AN

## Ignition IGBT

### 20 A, 400 V, N-Channel DPAK

This Logic Level Insulated Gate Bipolar Transistor (IGBT) features monolithic circuitry integrating ESD and Overvoltage clamped protection for use in inductive coil drivers applications. Primary uses include Ignition, Direct Fuel Injection, or wherever high voltage and high current switching is required.

#### Features

- Ideal for Coil-on-Plug and Driver-on-Coil Applications
- DPAK Package Offers Smaller Footprint for Increased Board Space
- Gate-Emitter ESD Protection
- Temperature Compensated Gate-Collector Voltage Clamp Limits Stress Applied to Load
- Integrated ESD Diode Protection
- Low Threshold Voltage for Interfacing Power Loads to Logic or Microprocessor Devices
- Low Saturation Voltage
- High Pulsed Current Capability
- These are Pb-Free Devices

#### Applications

- Ignition Systems

#### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                | Symbol            | Value       | Unit                     |
|---------------------------------------------------------------------------------------|-------------------|-------------|--------------------------|
| Collector-Emitter Voltage                                                             | $V_{CES}$         | 440         | V                        |
| Collector-Gate Voltage                                                                | $V_{CER}$         | 440         | V                        |
| Gate-Emitter Voltage                                                                  | $V_{GE}$          | $\pm 15$    | V                        |
| Collector Current-Continuous<br>@ $T_C = 25^\circ\text{C}$ - Pulsed                   | $I_C$             | 20<br>50    | $A_{DC}$<br>$A_{AC}$     |
| Continuous Gate Current                                                               | $I_G$             | 1.0         | mA                       |
| Transient Gate Current<br>( $t \leq 2$ ms, $f \leq 100$ Hz)                           | $I_G$             | 20          | mA                       |
| ESD (Charged-Device Model)                                                            | ESD               | 2.0         | kV                       |
| ESD (Human Body Model)<br>$R = 1500 \Omega$ , $C = 100$ pF                            | ESD               | 8.0         | kV                       |
| ESD (Machine Model) $R = 0 \Omega$ , $C = 200$ pF                                     | ESD               | 500         | V                        |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$             | 125<br>0.83 | W<br>W/ $^\circ\text{C}$ |
| Operating & Storage Temperature Range                                                 | $T_J$ , $T_{stg}$ | -55 to +175 | $^\circ\text{C}$         |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.




**ON Semiconductor®**

<http://onsemi.com>


**20 A, 400 V**

$V_{CE(on)} = 1.3 \text{ V @}$   
 $I_C = 10 \text{ A}, V_{GE} \geq 4.5 \text{ V}$



**DPAK**  
**CASE 369C**  
**STYLE 7**

#### MARKING DIAGRAM



Y = Year  
WW = Work Week  
NGD8201x = Device Code  
x = N or A  
G = Pb-Free Package

#### ORDERING INFORMATION

| Device       | Package           | Shipping†          |
|--------------|-------------------|--------------------|
| NGD8201NT4G  | DPAK<br>(Pb-Free) | 2500 / Tape & Reel |
| NGD8201ANT4G | DPAK<br>(Pb-Free) | 2500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NGD8201N, NGD8201AN

## UNCLAMPED COLLECTOR-TO-EMITTER AVALANCHE CHARACTERISTICS ( $-55^{\circ} \leq T_J \leq 175^{\circ}C$ )

| Characteristic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Symbol      | Value             | Unit |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------------------|------|
| Single Pulse Collector-to-Emitter Avalanche Energy<br>$V_{CC} = 50\text{ V}$ , $V_{GE} = 5.0\text{ V}$ , $Pk\ I_L = 16.7\text{ A}$ , $R_G = 1000\ \Omega$ , $L = 1.8\text{ mH}$ , Starting $T_J = 25^{\circ}C$<br>$V_{CC} = 50\text{ V}$ , $V_{GE} = 5.0\text{ V}$ , $Pk\ I_L = 14.9\text{ A}$ , $R_G = 1000\ \Omega$ , $L = 1.8\text{ mH}$ , Starting $T_J = 150^{\circ}C$<br>$V_{CC} = 50\text{ V}$ , $V_{GE} = 5.0\text{ V}$ , $Pk\ I_L = 14.1\text{ A}$ , $R_G = 1000\ \Omega$ , $L = 1.8\text{ mH}$ , Starting $T_J = 175^{\circ}C$ | $E_{AS}$    | 250<br>200<br>180 | mJ   |
| Reverse Avalanche Energy<br>$V_{CC} = 100\text{ V}$ , $V_{GE} = 20\text{ V}$ , $Pk\ I_L = 25.8\text{ A}$ , $L = 6.0\text{ mH}$ , Starting $T_J = 25^{\circ}C$                                                                                                                                                                                                                                                                                                                                                                            | $E_{AS(R)}$ | 2000              | mJ   |

## THERMAL CHARACTERISTICS

|                                                                                   |                 |     |               |
|-----------------------------------------------------------------------------------|-----------------|-----|---------------|
| Thermal Resistance, Junction-to-Case                                              | $R_{\theta JC}$ | 1.2 | $^{\circ}C/W$ |
| Thermal Resistance, Junction-to-Ambient (Note 1)                                  | $R_{\theta JA}$ | 95  | $^{\circ}C/W$ |
| Maximum Temperature for Soldering Purposes, 1/8" from case for 5 seconds (Note 2) | $T_L$           | 275 | $^{\circ}C$   |

- When surface mounted to an FR4 board using the minimum recommended pad size.
- For further details, see Soldering and Mounting Techniques Reference Manual: SOLDERM/D.

## ELECTRICAL CHARACTERISTICS

| Characteristic | Symbol | Test Conditions | Temperature | Min | Typ | Max | Unit |
|----------------|--------|-----------------|-------------|-----|-----|-----|------|
|----------------|--------|-----------------|-------------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                           |               |                                                    |                                        |       |       |      |            |
|-------------------------------------------|---------------|----------------------------------------------------|----------------------------------------|-------|-------|------|------------|
| Collector-Emitter Clamp Voltage           | $BV_{CES}$    | $I_C = 2.0\text{ mA}$                              | $T_J = -40^{\circ}C$ to $175^{\circ}C$ | 370   | 395   | 420  | V          |
|                                           |               | $I_C = 10\text{ mA}$                               | $T_J = -40^{\circ}C$ to $175^{\circ}C$ | 390   | 415   | 440  |            |
| Zero Gate Voltage Collector Current       | $I_{CES}$     | $V_{GE} = 0\text{ V}$ , $V_{CE} = 15\text{ V}$     | $T_J = 25^{\circ}C$                    |       | 0.1   | 1.0  | $\mu A$    |
|                                           |               |                                                    | $T_J = 175^{\circ}C$                   | 0.5   | 1.5   | 10   |            |
|                                           |               | $V_{CE} = 200\text{ V}$ ,<br>$V_{GE} = 0\text{ V}$ | $T_J = 175^{\circ}C$                   | 1.0   | 25    | 100* | $\mu A$    |
|                                           |               |                                                    | $T_J = -40^{\circ}C$                   | 0.4   | 0.8   | 5.0  |            |
| Reverse Collector-Emitter Clamp Voltage   | $BV_{CES(R)}$ | $I_C = -75\text{ mA}$                              | $T_J = 25^{\circ}C$                    | 30    | 35    | 39   | V          |
|                                           |               |                                                    | $T_J = 175^{\circ}C$                   | 35    | 39    | 45*  |            |
|                                           |               |                                                    | $T_J = -40^{\circ}C$                   | 30    | 33    | 37   |            |
| Reverse Collector-Emitter Leakage Current | $I_{CES(R)}$  | $V_{CE} = -24\text{ V} -$<br>NGD8201N              | $T_J = 25^{\circ}C$                    | 0.05  | 0.1   | 1.0  | mA         |
|                                           |               |                                                    | $T_J = 175^{\circ}C$                   | 1.0   | 5.0   | 10   |            |
|                                           |               |                                                    | $T_J = -40^{\circ}C$                   | 0.005 | 0.01  | 0.1  |            |
|                                           |               | $V_{CE} = -24\text{ V} -$<br>NGD8201AN             | $T_J = 25^{\circ}C$                    | 0.05  | 0.2   | 1.0  |            |
|                                           |               |                                                    | $T_J = 175^{\circ}C$                   | 1.0   | 8.5   | 25   |            |
|                                           |               |                                                    | $T_J = -40^{\circ}C$                   | 0.005 | 0.025 | 0.2  |            |
| Gate-Emitter Clamp Voltage                | $BV_{GES}$    | $I_G = \pm 5.0\text{ mA}$                          | $T_J = -40^{\circ}C$ to $175^{\circ}C$ | 12    | 12.5  | 14   | V          |
| Gate-Emitter Leakage Current              | $I_{GES}$     | $V_{GE} = \pm 5.0\text{ V}$                        | $T_J = -40^{\circ}C$ to $175^{\circ}C$ | 200   | 300   | 350* | $\mu A$    |
| Gate Resistor                             | $R_G$         |                                                    | $T_J = -40^{\circ}C$ to $175^{\circ}C$ |       | 70    |      | $\Omega$   |
| Gate-Emitter Resistor                     | $R_{GE}$      |                                                    | $T_J = -40^{\circ}C$ to $175^{\circ}C$ | 14.25 | 16    | 25   | k $\Omega$ |

### ON CHARACTERISTICS (Note 4)

|                                              |              |                                           |                      |     |     |      |                 |
|----------------------------------------------|--------------|-------------------------------------------|----------------------|-----|-----|------|-----------------|
| Gate Threshold Voltage                       | $V_{GE(th)}$ | $I_C = 1.0\text{ mA}$ , $V_{GE} = V_{CE}$ | $T_J = 25^{\circ}C$  | 1.5 | 1.8 | 2.1  | V               |
|                                              |              |                                           | $T_J = 175^{\circ}C$ | 0.7 | 1.0 | 1.3  |                 |
|                                              |              |                                           | $T_J = -40^{\circ}C$ | 1.7 | 2.0 | 2.3* |                 |
| Threshold Temperature Coefficient (Negative) |              |                                           |                      | 4.0 | 4.6 | 5.2  | mV/ $^{\circ}C$ |

\*Maximum Value of Characteristic across Temperature Range.

3. Pulse Test: Pulse Width  $\leq 300\ \mu S$ , Duty Cycle  $\leq 2\%$ .

# NGD8201N, NGD8201AN

## ELECTRICAL CHARACTERISTICS

| Characteristic | Symbol | Test Conditions | Temperature | Min | Typ | Max | Unit |
|----------------|--------|-----------------|-------------|-----|-----|-----|------|
|----------------|--------|-----------------|-------------|-----|-----|-----|------|

### ON CHARACTERISTICS (Note 4)

|                                 |              |                                                                  |                           |      |      |      |      |
|---------------------------------|--------------|------------------------------------------------------------------|---------------------------|------|------|------|------|
| Collector-to-Emitter On-Voltage | $V_{CE(on)}$ | $I_C = 6.5 \text{ A}, V_{GE} = 3.7 \text{ V} - \text{NGD8201N}$  | $T_J = 25^\circ\text{C}$  | 0.95 | 1.15 | 1.35 | V    |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.7  | 0.95 | 1.15 |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.0  | 1.3  | 1.4  |      |
|                                 |              | $I_C = 6.5 \text{ A}, V_{GE} = 3.7 \text{ V} - \text{NGD8201AN}$ | $T_J = 25^\circ\text{C}$  | 0.85 | 1.03 | 1.35 |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.7  | 0.9  | 1.15 |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 0.9  | 1.11 | 1.4  |      |
|                                 |              | $I_C = 9.0 \text{ A}, V_{GE} = 3.9 \text{ V} - \text{NGD8201N}$  | $T_J = 25^\circ\text{C}$  | 0.95 | 1.25 | 1.45 |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.8  | 1.05 | 1.25 |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.1  | 1.4  | 1.5  |      |
|                                 |              | $I_C = 9.0 \text{ A}, V_{GE} = 3.9 \text{ V} - \text{NGD8201AN}$ | $T_J = 25^\circ\text{C}$  | 0.9  | 1.11 | 1.45 |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.8  | 1.01 | 1.25 |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.0  | 1.18 | 1.5  |      |
|                                 |              | $I_C = 7.5 \text{ A}, V_{GE} = 4.5 \text{ V}$                    | $T_J = 25^\circ\text{C}$  | 0.85 | 1.15 | 1.4  |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.7  | 0.95 | 1.2  |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.0  | 1.3  | 1.6* |      |
|                                 |              | $I_C = 10 \text{ A}, V_{GE} = 4.5 \text{ V}$                     | $T_J = 25^\circ\text{C}$  | 1.0  | 1.3  | 1.6  |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 0.8  | 1.05 | 1.4  |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.1  | 1.4  | 1.7* |      |
|                                 |              | $I_C = 15 \text{ A}, V_{GE} = 4.5 \text{ V}$                     | $T_J = 25^\circ\text{C}$  | 1.15 | 1.45 | 1.7  |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 1.0  | 1.3  | 1.55 |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.25 | 1.55 | 1.8* |      |
|                                 |              | $I_C = 20 \text{ A}, V_{GE} = 4.5 \text{ V} - \text{NGD8201N}$   | $T_J = 25^\circ\text{C}$  | 1.3  | 1.6  | 1.9  |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 1.2  | 1.5  | 1.8  |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.4  | 1.75 | 2.0  |      |
|                                 |              | $I_C = 20 \text{ A}, V_{GE} = 4.5 \text{ V} - \text{NGD8201AN}$  | $T_J = 25^\circ\text{C}$  | 1.1  | 1.4  | 1.9  |      |
|                                 |              |                                                                  | $T_J = 175^\circ\text{C}$ | 1.2  | 1.5  | 1.8  |      |
|                                 |              |                                                                  | $T_J = -40^\circ\text{C}$ | 1.3  | 1.42 | 2.0  |      |
| Forward Transconductance        | gfs          | $I_C = 6.0 \text{ A}, V_{CE} = 5.0 \text{ V}$                    | $T_J = 25^\circ\text{C}$  | 10   | 18   | 25   | Mhos |

### DYNAMIC CHARACTERISTICS

|                      |           |                                             |                          |      |      |      |    |
|----------------------|-----------|---------------------------------------------|--------------------------|------|------|------|----|
| Input Capacitance    | $C_{iss}$ | $f = 10 \text{ kHz}, V_{CE} = 25 \text{ V}$ | $T_J = 25^\circ\text{C}$ | 1100 | 1300 | 1500 | pF |
| Output Capacitance   | $C_{oss}$ |                                             |                          | 70   | 80   | 90   |    |
| Transfer Capacitance | $C_{rss}$ |                                             |                          | 18   | 20   | 22   |    |

# NGD8201N, NGD8201AN

## ELECTRICAL CHARACTERISTICS

| Characteristic | Symbol | Test Conditions | Temperature | Min | Typ | Max | Unit |
|----------------|--------|-----------------|-------------|-----|-----|-----|------|
|----------------|--------|-----------------|-------------|-----|-----|-----|------|

### SWITCHING CHARACTERISTICS

|                                 |              |                                                                                                                                   |                           |     |      |     |                 |
|---------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------|-----|------|-----|-----------------|
| Turn-Off Delay Time (Resistive) | $t_{d(off)}$ | $V_{CC} = 300\text{ V}, I_C = 9.0\text{ A}$<br>$R_G = 1.0\text{ k}\Omega, R_L = 33\text{ }\Omega,$<br>$V_{GE} = 5.0\text{ V}$     | $T_J = 25^\circ\text{C}$  | 6.0 | 8.0  | 10  | $\mu\text{Sec}$ |
| Fall Time (Resistive)           | $t_f$        |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 6.0 | 8.0  | 10  |                 |
|                                 |              |                                                                                                                                   | $T_J = 25^\circ\text{C}$  | 4.0 | 6.0  | 8.0 |                 |
|                                 |              |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 8.0 | 10.5 | 14  |                 |
| Turn-Off Delay Time (Inductive) | $t_{d(off)}$ | $V_{CC} = 300\text{ V}, I_C = 9.0\text{ A}$<br>$R_G = 1.0\text{ k}\Omega,$<br>$L = 300\text{ }\mu\text{H}, V_{GE} = 5.0\text{ V}$ | $T_J = 25^\circ\text{C}$  | 3.0 | 5.0  | 7.0 |                 |
| Fall Time (Inductive)           | $t_f$        |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 5.0 | 7.0  | 9.0 |                 |
|                                 |              |                                                                                                                                   | $T_J = 25^\circ\text{C}$  | 1.5 | 3.0  | 4.5 |                 |
|                                 |              |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 5.0 | 7.0  | 10  |                 |
| Turn-On Delay Time              | $t_{d(on)}$  | $V_{CC} = 14\text{ V}, I_C = 9.0\text{ A}$<br>$R_G = 1.0\text{ k}\Omega, R_L = 1.5\text{ }\Omega,$<br>$V_{GE} = 5.0\text{ V}$     | $T_J = 25^\circ\text{C}$  | 1.0 | 1.5  | 2.0 |                 |
| Rise Time                       | $t_r$        |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 1.0 | 1.5  | 2.0 |                 |
|                                 |              |                                                                                                                                   | $T_J = 25^\circ\text{C}$  | 4.0 | 6.0  | 8.0 |                 |
|                                 |              |                                                                                                                                   | $T_J = 175^\circ\text{C}$ | 3.0 | 5.0  | 7.0 |                 |

\*Maximum Value of Characteristic across Temperature Range.

4. Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{S}$ , Duty Cycle  $\leq 2\%$ .

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Self Clamped Inductive Switching




Figure 2. Open Secondary Avalanche Current vs. Temperature




Figure 3. Collector-to-Emitter Voltage vs. Junction Temperature




Figure 4. Collector Current vs. Collector-to-Emitter Voltage




Figure 5. Collector Current vs. Collector-to-Emitter Voltage




Figure 6. Collector Current vs. Collector-to-Emitter Voltage

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 7. Transfer Characteristics




Figure 8. Collector-to-Emitter Leakage Current vs. Temperature




Figure 9. Gate Threshold Voltage vs. Temperature




Figure 10. Capacitance vs. Collector-to-Emitter Voltage




Figure 11. Resistive Switching Fall Time vs. Temperature






Figure 12. Inductive Switching Fall Time vs. Temperature

# NGD8201N, NGD8201AN



**Figure 13. Minimum Pad Transient Thermal Resistance  
(Non-normalized Junction-to-Ambient)**




**Figure 14. Best Case Transient Thermal Resistance  
(Non-normalized Junction-to-Case Mounted on Cold Plate)**

# NGD8201N, NGD8201AN

## PACKAGE DIMENSIONS

### DPAK CASE 369C ISSUE D



#### NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.086     | 0.094 | 2.18        | 2.38  |
| A1  | 0.000     | 0.005 | 0.00        | 0.13  |
| b   | 0.025     | 0.035 | 0.63        | 0.89  |
| b2  | 0.030     | 0.045 | 0.76        | 1.14  |
| b3  | 0.180     | 0.215 | 4.57        | 5.46  |
| c   | 0.018     | 0.024 | 0.46        | 0.61  |
| c2  | 0.018     | 0.024 | 0.46        | 0.61  |
| D   | 0.235     | 0.245 | 5.97        | 6.22  |
| E   | 0.250     | 0.265 | 6.35        | 6.73  |
| e   | 0.090 BSC |       | 2.29 BSC    |       |
| H   | 0.370     | 0.410 | 9.40        | 10.41 |
| L   | 0.055     | 0.070 | 1.40        | 1.78  |
| L1  | 0.108 REF |       | 2.74 REF    |       |
| L2  | 0.020 BSC |       | 0.51 BSC    |       |
| L3  | 0.035     | 0.050 | 0.89        | 1.27  |
| L4  | ---       | 0.040 | ---         | 1.01  |
| Z   | 0.155     | ---   | 3.93        | ---   |

#### STYLE 7:

- PIN 1. GATE
- COLLECTOR
- EMITTER
- COLLECTOR

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative