




NO. 4E350B-2022-A0




LABEL (铭牌):



WIRING DIAGRAM (接线图):




FLOW RATE CURVE (风量曲线):



WEIGUANG®

SPECIFICATION 规格说明
HANGZHOU WEIGUANG ELECTRONIC CO.,LTD.

UNIT 类型	Axial fan motor 外转子轴流风机
MOTOR 电机型式	Single phase motor with capacitor
MOTOR TYPE 电机型号	YWF4E-350B-102/34-G
VOLTAGE 额定电压 (V)	230
FREQUENCY 频率 (Hz)	50
INPUT POWER 输入功率 (W)	129
CURRENT 电流 (A)	0.65
SPEED 转速 (r/min)	1400
AIR FLOW 风量 20Pa (m³/h)	2300
NOISE 噪音 (dBA)	64
CAPACITOR 电容 (μ F/450V)	4
ROTATION 旋转方向	CCW ,looking into the end-shield 逆时针, 从端盖端方向看
INSULATION CLASS 绝缘等级	F
MOTOR PROTECTION 电机保护	Thermocontact 150±5℃ 热保护器
TEMPERATURE RISE 温升	75K max 运行温升不超过75K
	IP54
OPERATING TYPE 工作定额	S1 连续工作制
AMBIENT TEMPERATURE 适用环境温度	-30℃ +60℃
BEARINGS 轴承型式	Ball bearings 滚珠轴承
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
ELECTRICAL CONNECTION 电源线	Lead wire RV-90 4G 0.50mm² ,Length 1500±15mm 斜出线 (4芯0.5mm²线长1500±15mm)
APPROVALS 认证标记	CCC、CE
NET WEIGHT/GROSS WEIGHT净重/毛重	5.0/6.0kg
PACKING 包装	38.5*38.5*15.5cm

REV.	DESCRIPTION	APPROVED	DATE	DRN. BY	SIGN	DATE	TITLE
				CHD. BY			YWF4E-350B-102/34-G
				ENG. BY			PROJECTION 
				APP. BY			A4 SCALE SHEET: of