

LD-320

32" Industrial Open Frame LCD Monitor



Features

- Flexible, low cost and high performance
- For kiosk, gaming, amusement, digital signage application
- 31.5" 16:9 WUXGA TFT LCD display
- Premium MVA with wide-view angle
- VESA mount



Specifications

LCD panel	Size	32" (16:9)
	Backlight	LED (30K hours)
	Panel type	Premium MVA
	Pixel pitch	0.36375 mm
	Active area	698.4x392.85 mm
	Brightness	350 cd/m2
	Contrast	3000 : 1
	Viewing angle	178 / 178 degree
	Resolution	1920 x 1080
	Display color	16.7M (8 bit)
Video	Response time	6.5 mS (gray-gray)
	Hor. frequency	30 ~ 86 KHz
	Ver. frequency	60/70 Hz
	Pixel rate	165 MHz

Signal input	VGA, DVI-I	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	AC input	100~240Vac, 1A
	Inrush current	30A (cold start)
	Consumption	60W
	Management	VESA DPMS
Mounting	200x200mm VESA mount	
Dimension	763.4 (W) x 453.4 (H) x 106.4 (D) mm	
Net weight	G.W	13 Kg
	N.W	11 Kg
Package	Packing	1 pcs / carton
	Carton size	
	Container loading	
Temperature	Operation *	0 ~ 50 degree C
	Storage	-30 ~ 70 degree C

* Temperature of LCD surface

Ordering information

Model selection

LD-320-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	P: Projective capacitive
	...etc. Specified LCD	P: DVI/HDMI/DP	I: IR
		S: VGA/DVI/S-video	S: SAW

Optional accessories

- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing

