

LD-104

10.4" Industrial Open Frame LCD Monitor

Features

- Flexible, low cost and high performance
- For industrial, kiosk, gaming, digital signage application
- 10.4" SVGA TFT LCD display
- VESA mount



Specifications

| | | |
|-----------|----------------|----------------------|
| LCD panel | Size | 10.4" (4:3) |
| | Backlight | LED |
| | Panel type | TN |
| | Pixel pitch | 0.264x0.264 mm |
| | Active area | 211.2x158.4 mm |
| | Brightness* | 400 cd/m2 max. |
| | Contrast | 700 : 1 |
| | Viewing angle | 80/80/60/70 degree |
| | Resolution | 800 x 600 |
| | Display color | 262K/16.2M (6/8 bit) |
| Video | Response time | Tr/Tf=10/5 mS |
| | Hor. frequency | 30 ~ 48 KHz |
| | Ver. frequency | 60/70 Hz |
| | Pixel rate | 50 MHz |

| | | |
|----------------|---------------------------------|-------------------|
| Signal input | 15 pin D-sub connector for VGA | |
| OSD adjustment | Power, Enter, Left, Right, Auto | |
| Power | DC connector | 2.5mm diameter |
| | DC input | 12 Vdc / 0.7A |
| | Consumption | 8W |
| | Management | VESA DPMS |
| Mounting | 75x75mm VESA mount | |
| Dimension | 233.5 (W) x 180 (H) x 41 (D) mm | |
| Net weight | | |
| Package | Packing | 5 pcs / carton |
| | 20' container | |
| | 40' container | |
| Temperature | Operation** | -30 ~ 80 degree C |
| | Storage | -30 ~ 80 degree C |

* Different brightness is per customer's request

** Temperature of LCD surface

** Different temperature range is on demand.

Ordering information

■ Model selection

| LD-104-XYZ | X: Panel selection | Y: Input selection | Z: Touch selection |
|------------|-----------------------|----------------------|--------------------------|
| | 0: Standard, chosen | 0: Standard, VGA/DVI | 0: Standard, none |
| | A: Specified LCD | V: VGA only | G: Glass |
| | B: Specified LCD | H: VGA/DVI/HDMI | R: Resistive |
| | ...etc. Specified LCD | P: DVI/HDMI/DP | C: Surface capacitive |
| | | S: VGA/DVI/S-video | P: Projective capacitive |
| | | | I: IR |
| | | | S: SAW |

■ Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing

