

LD-057

5.7" Industrial Open Frame LCD Monitor

Features

- Flexible, low cost and high performance
- For industrial, kiosk, information application
- 5.7" VGA TFT LCD display
- VESA mount

Specifications

LCD panel	Size	5.7" (4:3)	
	Backlight	LED	
	Panel type	TN	
	Pixel pitch	0.18x0.18 mm	
	Active area	115.2x86.4 mm	
	Brightness	500 cd/m2 *	
	Contrast	250 : 1	
	Viewing angle	140 / 100 degree	
	Resolution	640 x 480	
	Display color	262K (6 bit)	
	Response time	Tr/Tf=50 mS	
	Video	Hor. frequency	30 ~ 38 KHz
		Ver. frequency	60/70 Hz
Pixel rate		40 MHz	

* 1000 cd/m2 is on demand.



Signal input	15 pin D-sub connector for VGA	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	DC connector	2.5mm diameter
	DC input	12 Vdc / 0.5A
	Consumption	6W
	Management	VESA DPMS
Mounting	75x75mm VESA mount	
Dimension	184 (W) x 119 (H) x 41.5 (D) mm	
Net weight		
Package	Packing	24 pcs / carton
	20' container	
	40' container	
Temperature	Operation	-20 ~ 70 degree C
	Storage	-30 ~ 80 degree C

Ordering information

■ Model selection

LD-057-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	R: Resitive
	...etc. Specified LCD	P: DVI/HDMI/DP	C: Surface capacitive
		S: VGA/DVI/S-video	P: Projective capacitive
			I: IR
			S: SAW

■ Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 1A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable

Product drawing (referenced only, to be renewed)

