

LD-170

17" Industrial Open Frame LCD Monitor

Features

- Flexible, high brightness and high performance
- For industrial, kiosk, gaming, digital signage application
- 17" SXGA TFT LCD display
- VESA mount



Specifications

LCD panel *	Size	17" (5:4)
	Backlight	LED (30K hours)
	Panel type	TN
	Pixel pitch	0.264x0.264 mm
	Active area	337.92x270.34 mm
	Brightness *	350 cd/m2
	Contrast	1000 : 1
	Viewing angle	85/85/80/80 degree
	Resolution	1280 x 1024
	Display color	16.7M (8 bit)
	Response time	Tr/Tf=3.5/1.5 mS
Video	Hor. frequency	30 ~ 80 KHz
	Ver. frequency	60/70/75 Hz
	Pixel rate	135 MHz

* Different brightness is per customer's request

Signal input	D-sub 15P VGA, 24+5P DVI	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	DC connector	2.5mm diameter
	DC input	12 Vdc / 1.5A
	Consumption	18W
Management	VESA DPMS	
Mounting	75x75, 100x100mm VESA mount	
Dimension	367 (W) x 299.5 (H) x 50 (D) mm	
Net weight	4.3 kg	
Package	Packing	3 pcs / carton
	Carton size	450x295x457mm
	Container loading	960/20', 2,112/40'
Temperature	Operation **	0 ~ 50 degree C
	Storage	-30 ~ 80 degree C

** Temperature of LCD surface

** Wider temperature -30 ~ 85 degree C is on demand.

Ordering information

■ Model selection

LD-170-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	R: Resistive
	...etc. Specified LCD	P: DVI/HDMI/DP	C: Surface capacitive
		S: VGA/DVI/S-video	P: Projective capacitive
			I: IR
			S: SAW

■ Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing

