

# LD-460

## 46" Narrow Band Industrial Open Frame LCD Monitor

### Features

- Flexible, low cost and high performance
- For kiosk, gaming, amusement, digital signage application
- 46" 16:9 WUXGA TFT LCD display
- Premium MVA with wide-view angle
- VESA mount



### Specifications

LCD panel	Size	46" (16:9)
	Backlight	LED
	Panel type	Premium MVA
	Pixel pitch	0.17675 x 0.53025 mm
	Active area	1018.08x572.67 mm
	Brightness	700 cd/m2
	Contrast	4000 : 1
	Viewing angle	178 / 178 degree
	Resolution	1920 x 1080
	Display color	16.7M (8 bit)
	Response time	6.5 mS (gray-gray)
Video	Hor. frequency	30 ~ 86 KHz
	Ver. frequency	60/70/75 Hz
	Pixel rate	165 MHz

Signal input	VGA, DVI-I	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	AC input	100~240Vac, 2A
	Inrush current	35A (cold start)
	Consumption	120W
	Management	VESA DPMS
Mounting	400x300mm M6 screw	
Dimension	1054.8 (W) x 609.4 (H) x 85 (D) mm	
Weight	G.W : 35 Kg	N.W : 32 Kg
	Packing	1 pcs / carton
Package	Carton size	
	Container loading	
Temperature	Operation *	0 ~ 50 degree C
	Storage	-30 ~ 70 degree C

\* Temperature of LCD surface

### Ordering information

#### ■ Model selection

LD-460-XYZ	<b>X:</b> Panel selection	<b>Y:</b> Input selection	<b>Z:</b> Touch selection
	<b>0:</b> Standard, chosen	<b>0:</b> Standard, VGA/DVI	<b>0:</b> Standard, none
	<b>A:</b> Specified LCD	<b>V:</b> VGA only	<b>G:</b> Glass
	<b>B:</b> Specified LCD	<b>H:</b> VGA/DVI/HDMI	<b>P:</b> Projective capacitive
	<b>...etc.</b> Specified LCD	<b>P:</b> DVI/HDMI/DP	<b>I :</b> IR
	<b>S:</b> VGA/DVI/S-video	<b>S:</b> SAW	

#### ■ Optional accessories

- \* Power cord                    1.8M power cord, US / EU
- \* Signal cable                 1.8M VGA cable, 1.8M DVI cable

### Product drawing

