

HA-170

17" High brightness open frame LCD monitor with auto-dimming

Features

- High brightness with auto-dimming control (energy saving)
- For kiosk, outdoor, semi-outdoor, digital signage application
- 17" SXGA TFT LCD with LED backlight
- Removable environment light sensor
- VESA mount (75x75, 100x100mm)
- RS232 for remote control



Specifications

LCD panel	Size	17" (5:4)
	Backlight	LED
	Panel type	TN
	Pixel pitch	0.264x0.264 mm
	Active area	337.92x270.34 mm
	Brightness	1000 cd/m2 *
	Contrast	1000 : 1
	Viewing angle	170 / 160 degree
	Resolution	1280 x 1024
	Display color	16.7M (6 bit+HiFRC)
	Response time	Tr/Tf=3.5/1.5 mS
Video	Hor. frequency	30 ~ 80 KHz
	Ver. frequency	60/70/75 Hz
	Pixel rate	135 MHz

Signal input	VGA, DVI-I	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	DC connector	2.5mm diameter
	DC input	12 Vdc / 2.5A
	Consumption	30W
	Management	VESA DPMS
Mounting	75x75, 100x100mm VESA mount	
Dimension	367 (W) x 299.5 (H) x 50 (D) mm	
Net weight	3.9 kg	
Package	Packing	3 pcs / carton
	Carton size	450x295x457mm
	Container loading	
Temperature	Operation	-20 ~ 60 degree C
	Storage	-30 ~ 80 degree C

* Higher brightness is on demandt.

Ordering information

Model selection

HA-170-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	R: Resistive
	.. etc. Specified LCD	P: DVI/HDMI/DP	C: Surface capacitive
		S: VGA/DVI/S-video	P: Projective capacitive
			I: IR
			S: SAW

Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable, 1.8M RS232 cable

Product drawing

