

LD-240

24" Industrial Open Frame LCD Monitor

Features

- Flexible, low cost and high performance
- For industrial, kiosk, gaming, digital signage application
- 24" 16:9 WUXGA TFT LCD display
- VA with wide-view angle
- VESA mount



Specifications

LCD panel	Size	24" (16:9)
	Backlight	LED
	Panel type	VA
	Pixel pitch	0.277x0.277 mm
	Active area	531.36x298.89 mm
	Brightness	300 cd/m2
	Contrast	5000 : 1
	Viewing angle	178 / 178 degree
	Brightness*	1920 x 1080
	Display color	16.7M (8 bit)
Video	Response time	Tr+Tf=25 mS
	Hor. frequency	30 ~ 86 KHz
	Ver. frequency	60/70 Hz
	Pixel rate	165 MHz

* Different brightness is per customer's request

Signal input	VGA, DVI-I	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	DC connector	2.5mm diameter
	DC input	12 Vdc / 3A
	Consumption	36W
	Management	VESA DPMS
Mounting	75x75, 100x100mm VESA mount	
Dimension	564.4 (W) x 333.2 (H) x 50 (D) mm	
Net weight		
Package	Packing	3 pcs / carton
	Carton size	
	Container loading	
Temperature	Operation**	0 ~ 50 degree C
	Storage	-30 ~ 70 degree C

** Temperature of LCD surface

** Different temperature range is on demand.

Ordering information

Model selection

LD-240-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	R: Resistive
	...etc. Specified LCD	P: DVI/HDMI/DP	C: Surface capacitive
		S: VGA/DVI/S-video	P: Projective capacitive
			I: IR
			S: SAW

Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing

