

LD-150

15" Industrial Open Frame LCD Monitor

Features

- Flexible, low cost and high performance
- For industrial, kiosk, gaming, digital signage application
- 15" XGA TFT LCD display
- VESA mount



Specifications

| | | |
|-----------|----------------|--------------------|
| LCD panel | Size | 15" (4:3) |
| | Backlight | LED (30K hours) |
| | Panel type | TN |
| | Pixel pitch | 0.297x0.297 mm |
| | Active area | 304.13x228.1 mm |
| | Brightness* | 400 cd/m2 max. |
| | Contrast | 800 : 1 |
| | Viewing angle | 80/80/80/80 degree |
| | Resolution | 1024 x 768 |
| | Display color | 16.2M (8 bit) |
| | Response time | Tr/Tf=5/11 mS |
| Video | Hor. frequency | 30 ~ 57 KHz |
| | Ver. frequency | 60/70 Hz |
| | Pixel rate | 75 MHz |

| | | |
|----------------|---------------------------------|--------------------|
| Signal input | D-sub 15P VGA, 24+5P DVI | |
| OSD adjustment | Power, Enter, Left, Right, Auto | |
| Power | DC connector | 2.5mm diameter |
| | DC input | 12 Vdc / 1.3A |
| | Consumption | 15W |
| Management | VESA DPMS | |
| Mounting | 75x75, 100x100mm VESA mount | |
| Dimension | 335 (W) x 256.5 (H) x 45 (D) mm | |
| Net weight | 3.1 kg | |
| Package | Packing | 3 pcs / carton |
| | Carton size | 420x280x415mm |
| | Container loading | 960/20', 2,112/40' |
| Temperature | Operation** | -20 ~ 70 degree C |
| | Storage | -30 ~ 80 degree C |

* Different brightness is per customer's request

** Temperature of LCD surface

** Wider temperature -30 ~ 85 degree C is on demand.

Ordering information

■ Model selection

| LD-150-XYZ | X: Panel selection | Y: Input selection | Z: Touch selection |
|------------|-----------------------|----------------------|--------------------------|
| | 0: Standard, chosen | 0: Standard, VGA/DVI | 0: Standard, none |
| | A: Specified LCD | V: VGA only | G: Glass |
| | B: Specified LCD | H: VGA/DVI/HDMI | R: Resistive |
| | ...etc. Specified LCD | P: DVI/HDMI/DP | C: Surface capacitive |
| | | S: VGA/DVI/S-video | P: Projective capacitive |
| | | | I: IR |
| | | | S: SAW |

■ Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing

