

Track System Specification

MT11S-42

— MicroTrack 11 series





◎ Basic Parameters

- Material: AL6063, spraying surface
- Coating: Matte Black (RAL9005)/ Matte White (RAL9003)/ Matte Silver (RAL9006)/ Champagne Gold (RAL1035)
- Size: $\phi 42 \times 80 \text{mm}$
- IP grade: IP20
- CCT: 2700K, 3000K, 4000K optional
- CRI: 90
- SDCM: <3 Step
- Beam angle: $15^\circ, 24^\circ, 36^\circ, 50^\circ$
- Light efficiency: 75 LM/W, 73 LM/W, 75 LM/W, 75 LM/W
- Input voltage: DC24-48V
- Lighting direction: Downward
- Dimming method: Non-dimming, DALI-2, Tuya Bluetooth, CASAMBI
- Application: Indoor
- Certification: CE, UKCA, ROHS, Reach
- Warranty: 5 years



◎ Product mechanical data







©Luminaire Parameters

Version	Model	Size	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	MT11S-42	φ42*80mm	24-48VDC	0.229	10.0	11	>90	15°	2700K	720
									3000K	750
									4000K	800
Normal	MT11S-42	φ42*80mm	24-48VDC	0.229	10.0	11	>90	24°	2700K	700
									3000K	730
									4000K	775
Normal	MT11S-42	φ42*80mm	24-48VDC	0.229	10.0	11	>90	36°	2700K	720
									3000K	750
									4000K	800
Normal	MT11S-42	φ42*80mm	24-48VDC	0.229	10.0	11	>90	50°	2700K	720
									3000K	750
									4000K	800

Note:

1. The output data is based on the testing result of Ra90,3000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

©Optical Parameter



[Points to note]

⚡ 48V Power Supply



Total track Length $\leq 50M$

⚡ 48V Power Supply






Max. Load $\leq 480W$

Supplementary power supplies are needed beside the Spotlights module / Decorative module / Linear modular under below one conditions:

1. Load $> 480W$ on the track
2. Total track length $> 50M$

◎ Accessories Information

Picture	Name	Model
	Trimless recessed track (13mm gypsum board)	TLS-MT11-RX0
	Ceiling track	TLS-MT11-SX0
	Pendant track	TLS-MT11-HX0
	Pendant track	TLS-MT11-SRX0
	φ1000mm 90° Ceiling curve track	TLS-MS111090
	Rail energization box	TLS-MT1101
	Horizontal corner power-on connectors	TLS-MT1102
	Flexible energized connectors	TLS-MT1103
	Rail energized connectors	TLS-MT1104
	Pendant accessory	TLS-MT1105
	Rail connectors	TLS-MT1106
	End caps	TLS-MT11-R-EC
	End caps	TLS-MT11-S-EC
	End caps	TLS-MT11-H-EC

Picture	Name	Model
	End caps	TLS-MT11-SR-EC
	L-shaped (Inward)	MT11-L90N-MS11
	L-shaped (Downward)	MT11-L90-MS11
	L-shaped (Inward)	MT11-L90N-MR11
	L-shaped (Downward)	MT11-L90-MR11
	L-shaped (Inward)	MT11-L90N-MH11
	L-shaped (Downward)	MT11-L90-MH11
	L-shaped (Downward)	MT11-L90-MSR11
	48V Constant Voltage Power supply(external)	BN-V48-XXXP
	48V Constant Voltage Power supply(build-in)	LV100W48CG MICRO

Note:

1,Please refer to the accessory list table for detailed parameters.

2,Different tracks need to be used with corresponding accessories

◎Packing

Model	Size (mm/box)	Quantity /box	Quantity /carton	NW (kg/box)	NW (kg/carton)	GW (kg)	Size (mm/carton)
TLS-MT11S42-XXX	200*100*50 [7.87"*3.94"*1.97"]	1	60	0.29	17.22	18.24	520*415*325 [20.47"*16.34"*12.80"]

◎Model Code

TLS	-	M	T	11	S	42	-	10	90	40	36	-	N	B	B
System TLS Track Light System		Series M: Magnetic Module	Installation T: Track	Track Size 11: 11mm	Type S: Spotlight	Size 42: ϕ 42mm		Type Power 10: 10W	CRI 90: Ra>90	CCT 27: 2700K 30: 3000K 40: 4000K	Beam angle 15: 15° 24: 24° 36: 36° 50: 50°		Dimming Method N: Non-Dimming D: 1-10V Dimming A: DALI Dimming X: No Power	Color B: Black	Inner Ring Color B: Black

◎Attentions

- 1、 Non-professionals are prohibited from installing, disassembling and repairing the product.
- 2、 Avoid scratching, distortion and irregular bending of the product during installation; otherwise it may cause irreparable damage to the product.
- 3、 Please use professional cutting tools when cutting
- 4、 Do not use any acid or alkaline adhesive to fix products
- 5、 The product is only suitable for indoor dry places, can not be used in outdoor, seaside or wet environment.
- 6、 PC features: Each 10°C rise or drop will make diffuser extend or shrink 0.8mm/m, please confirm before processing and use