# **GE-100 Gigabit Ethernet Adapter for PCI Bus**

# GE-100 is Gigabit (1000-baseT) PCI adapter based on the Realtek RTL8169 chip

The GE-100 Gigabit Ethernet Adapter CPI is a 32-bit LAN adapter for use in personal computers with a Peripheral Component Interconnect (PCI revision 2.2 or later) computer bus.

This adapter is a Tri-speed adapter that features a single RJ45 connector for either a 10 Mbps (megabits per second) IEEE 802.3 or 100Mbps IEEE 802.3u or 1000Mbps IEEE 802.3ab Ethernet network connection over unshielded twisted-pair (UTP) cable. The adapter can automatically negotiate 10/100/1000 Mbps, full or half duplex.



#### **Adapter Features**

The features of the Fast Ethernet PCI adapter include:

- · High performance bus master operation with low processor utilization
- · Automatically senses 10/100/1000 Mbps (10base-T/100base-T/1000base-T) connection and configures the speed accordingly
- $\cdot$  Auto negotiation or software configurable to operate in full-duplex mode, increasing aggregate bandwidth up to 2000 Mbps
- · Status LED's indicates link up, link speed and network activity
- · Automatic crossover support for crossover or regular cabling
- · UTP Category 5 cabling

## **Operating Environment**

• Power: +3.3VDC @ 378mA max.

Operating Temperature: 0°C to 50°C
Storage Temperature: -25°C to 70°C

Operating Humidity: 10% to 70% (non-condensing)
Storage Humidity: 10% to 90% (non-condensing)

# Product Specifications

# **Physical Specifications**

- · PCB mounted low profile RJ-45 connector
- · LED indicators for: link status, speed, network activity
- · Dimensions: 120mm x 58mm (4.72" x 2.0")

### Warranty

·2 years

### Cabling

- · Category 5 unshielded twisted pair
- · Maximum cable length 100m (325 ft)

Novolitovskaya str 15A, St. Petersburg 194100, Russia

Tel: +7 812 317 7103

info@spec-asu.ru

www.spec-asu.ru