



PISO-DA4U/DA8U/DA16U

- Universal PCI, 4-ch, 14-bit Isolated Analog Output Board
- Universal PCI, 8-ch, 14-bit Isolated Analog Output Board
- Universal PCI, 14-bit, 16-ch Isolated Analog Output Board

Introduction

The PISO-DA4U/DA8U/DA16U card is designed as an easy replacement for the PIO-DA4/DA8/DA16 without requiring any modification to the software or the driver.

The PISO-DA4U/DA8U/DA16U series provides an additional high-voltage isolation design that protects the Host PC from damage due to unexpected power surges, while the built-in high-quality isolation components provide the boards with 2500 Vdc bus-type isolation. The voltage output range for the PISO-DA4U/DA8U/DA16U series is from -10 V to +10 V, and the current output range is from 0 to 20 mA.

In addition, the PISO-DA4U/DA8U/DA16U series also features the following innovative advantages:

1. Accurate and easy-to-use calibration:

ICP DAS provides a software calibration function rather than manual calibration so that jumpers and trim-pots are no longer required for calibration, and the calibration data can be saved in the EEPROM for long-term use.

2. Individual channel configuration:

Each channel can be individually configured as either voltage or current output.

3. Card ID:

ICP DAS has also included an onboard Card ID switch on the PISO-DAxU series that enables the board to be recognized via software if two or more boards are installed in the same computer.

Software

Drivers

- 32/64-bit Windows XP/2003/2008/7/8/10
- Linux DASyLab

Sample Programs

- DOS Lib and TC/BC/MSC Demo LabVIEW Toolkit
- VB/VC/Delphi/BCB/VB.NET/C#.NET/VC.NET/MATLAB Demo

Ordering Information

PISO-DA4U CR	Universal PCI, 4-ch, 14-bit Isolated Analog Output Board (RoHS) Includes one CA-4002 D-Sub connector
PISO-DA4U/S CR	Universal PCI, 4-ch Isolated Analog Output Board (RoHS) Includes one CA-3710 D-Sub cable
PISO-DA8U CR	Universal PCI, 8-ch, 14-bit Isolated Analog Output Board (RoHS) Includes one CA-4002 D-Sub connector
PISO-DA8U/S CR	Universal PCI, 8-ch Isolated Analog Output Board (RoHS) Includes one CA-3710 D-Sub cable
PISO-DA16U CR	Universal PCI, 14-bit, 16-ch Isolated Analog Output Board (RoHS) Includes one CA-4002 D-Sub connector
PISO-DA16U/S CR	Universal PCI, 16-ch Isolated Analog Output Board (RoHS) Includes one CA-3710 D-Sub cable

Features

- Universal PCI (3.3 V/5 V) Interface
- 14-bit, 4/8/16-channel Analog Output
 - 2500 Vdc Bus and Power Isolation Protection
 - Built-in DC/DC Converter with 3000 Vdc Protection
 - Software Calibration
 - Two Timer-triggered Interrupt Sources
 - Double-buffered DA Latch
- Supports Card ID (SMD Switch)
- 16-channel 5 V/TTL Digital Output
- 16-channel 5 V/TTL Digital Input
 - Pull-high and Pull-low Function for DI Channels



Hardware Specifications

Model	PISO-DA4U	PISO-DA8U	PISO-DA16U
Hardware			
Card ID	Yes (4-bit)		
Connector	Female DB37 x 1 20-pin Box header x 2		
Analog Output			
Channels	4	8	16
Range	Voltage: ±10 V Current: 0 ~ 20 mA		
Resolution	14-bit		
Accuracy	0.04% of FSR ±2 LSB @ 25 °C, ± 10 V		
Voltage Output Capability	±5 mA		
Response Time	333 kHz (Typical)		
Slew Rate	0.71 V/μs		
Isolation	2500 V (Bus Type)		
Operation Mode	Static Update		
Digital I/O			
Channels	16		
Type	5 V/TTL		
TTL Input, ON Voltage Level	2.0 V Min.		
TTL Input, OFF Voltage Level	0.8 V Max.		
Response Speed	1.0 MHz (Typical)		
Trigger Mode	Static Update		
Digital Output			
Channels	16		
Type	5 V/TTL		
Operation Mode	Static Update		
Voltage	Logic 0: 0.4 V Max. Logic 1: 2.4 V Min.		
Max. Load Current	Sink: 2.4 mA @ 0.8 V Source: 0.8 mA @ 2.0 V		
Response Speed	1.0 MHz (Typical)		
Timer/Counter/Frequency			
Channels	3		
Type	5 V/TTL		
Resolution	16-bit		
Reference Clock	Internal: 4 MHz		
PC Bus			
Type	3.3 V/5 V Universal PCI, 32-bit, 33 MHz		
Data Bus	8-bit		
Power			
Consumption	2200 mA @ +5 V	2400 mA @ +5 V	3000 mA @ +5 V
Mechanical			
Dimensions (mm)	105.1 x 188 x 22 (W x L x D)		105.06 x 188 x 22 (W x L x D)
Power			
Operating Temperature	0 ~ +60°C		
Storage Temperature	-20 ~ +70°C		
Humidity	5 ~ 85% RH, Non-condensing		

Pin Assignments

Pin Assignment	Terminal No.	Pin Assignment	Terminal No.	Pin Assignment
VO_0	01	IO_0	20	DO 0
VO_1	02	IO_1	21	DO 2
VO_2	03	IO_2	22	DO 4
VO_3	04	IO_3	23	DO 6
A.GND	05	A.GND	24	DO 8
VO_4	06	IO_4	25	DO 10
VO_5	07	IO_5	26	DO 12
VO_6	08	IO_6	27	DO 14
VO_7	09	IO_7	28	GND
A.GND	10	A.GND	29	+5 V
VO_8	11	IO_8	30	CON1
VO_9	12	IO_9	31	
VO_10	13	IO_10	32	
VO_11	14	IO_11	33	
A.GND	15	IO_12	34	
VO_12	16	IO_13	35	
VO_13	17	IO_14	36	
VO_14	18	IO_15	37	
VO_15	19			
CON3				

Pin Assignment	Terminal No.	Pin Assignment
DI 0	01	DI 1
DI 2	03	DI 3
DI 4	05	DI 5
DI 6	07	DI 7
DI 8	09	DI 9
DI 10	10	DI 11
DI 12	12	DI 13
DI 14	14	DI 15
GND	16	GND
+5 V	18	+12 V

Accessories

	ADP-20/PCI	Extender, Extended dual 20-pin flat-cable connector to PC slot window
	CA-2002	20-pin flat cable, 20 cm x 2
	CA-2010	20-pin flat cable, 1 M
	CA-2020	20-pin flat cable, 2 M.
	CA-3710	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (45°))
	CA-3710D	DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (180°))
	CA-3715DM-H	DB-37 Male-Male Cable, 1.5 M, 180°. (RoHS)
	CA-3730DM-H	DB-37 Male-Male Cable, 3.0 M, 180°. (RoHS)
	CA-3750DM	DB-37 Male-Male Cable, 5.0 M, 180°. (RoHS)
	CA-3750DM-H	DB-37 Male-Male Cable, 5.0 M, 180°. (RoHS)
	CA-4002	37-pin Male D-sub connector with plastic cover.
	DB-16P	16-channel Isolated Digital Input Daughter Board
	DB-16R	16-channel Relay Output Daughter Board
	DB-24PR	24-channel power relay board
	DB-24POR	24-channel Photo Mos relay output board
	DB-24C	24-channel open-collector output board
	DN-20/DN-20-381	20-pin DIN-RAIL mounting I/O connector board
	DN-37	DIN Rail Mounting 37-pin Connector

