



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

# AIMOL X-Cool Plus 22

AIMOL X-Cool Plus 22 – ( )

AIMOL X-Cool Plus 22 2-8%

- ◆ 2-3%-
- ◆ 3-5%-
- ◆ 3-7%-
- ◆ 5-8%-
- ◆ 4-7%-

10%

- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆

( 500 ppm)

AIMOL X-Cool Plus 22

- ◆
- ◆
- ◆



## ТЕХНИЧЕСКОЕ ОПИСАНИЕ

### AIMOL X-Cool Plus 22

AIMOL X-Cool Plus 22

- ◆ DIN 51385 2.1 (SEM)
- ◆ ISO 6743/7 L-MAB

AIMOL X-Cool Plus 22

25° , 60 . 50° 100-500 ppm 5-30- TDS- 0,1 / . 1,33. % = 5%. x 1,3;

AIMOL X-Cool Plus 22 -15°

(280 ppm)

, AIMOL X-Cool Plus 22

0 +35°

	X-Cool Plus 22
, %	<20
50° ,	74.1
, %	
20° , / 3	1.0293

5% (

280 ppm)

	X-Cool Plus 22
pH	9.9
) 3% 5 (	
3% -4	
	150
	100

AIMOL X-Cool Plus 22 –

AIMOL,



## ТЕХНИЧЕСКОЕ ОПИСАНИЕ

### AIMOL X-Cool Plus 22

AIM b.v.

ANGLO INTERNATIONAL MINING B.V.  
Haringvliet 543, 3011 ZP Rotterdam  
The Netherlands  
T +31 (0)10 28 27 927  
info@aimol.nl

[www.aimol.nl](http://www.aimol.nl)

[www.aimol.ru](http://www.aimol.ru)

«  
127550  
44, 2  
+7 (495) 602 01 74  
info@aimol.ru