Specifications



Photo is representative

Eaton DILM25-01(208V60HZ)

Eaton XT IEC large contactor, 25A, 208 Vac, 60 Hz, 1NC, 25A, Frame C, 45 mm, 60 Hz, 2, 5/7.5, 10, 15, 20 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Screw terminals, Full voltage non-reversing miniature contactor, 400V, 11 kW

General specifications		
PRODUCT NAME	Eaton XT IEC large contactor	
CATALOG NUMBER	DILM25-01(208V60HZ)	
EAN	4015082771584	
PRODUCT LENGTH/DEPTH	138 mm	
PRODUCT HEIGHT	85 mm	
PRODUCT WIDTH	56.3 mm	
PRODUCT WEIGHT	0.01 lb	
COMPLIANCES	CE Marked RoHS Compliant	
CERTIFICATIONS	IEC 60947 CSA Certified EN 60947 UL Listed	



Product specifications		
AMPERAGE RATING	25A	
HP RATING - MAX	2, 5/7.5, 10, 15, 20 (1/3PH @120,240/208,240,480,600 V)	
NUMBER OF POLES	Three-pole	
ТҮРЕ	Full voltage non-reversing miniature contactor	
VOLTAGE RATING	400 V	
FREQUENCY RATING	60 Hz	
CONNECTION	Screw connection	
FRAME SIZE	45 mm	
TERMINALS	Screw terminals	
COIL VOLTAGE	208 Vac, 60 Hz	
CONTACT CONFIGURATION	1 NC	
CONTINUOUS AMPERE RATING	25 A	
SERIES	XT IEC	
NUMBER OF CONTACTS	1 NC	
OPERATION	Non-reversing	
POWER CONSUMPTION	11 kW	

Resources	
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors
	Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DILM25-01(208V60HZ)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









