





LABEL (铭牌):

Axial Fan Motor


YWF6D-800S-180/75-G

△ 400V 50Hz 2.85A 968/1200W 920r/min


Y 400V 50Hz 1.65A 730/930W 770r/min

CL.F IP54 XX/XX

WIRING DIAGRAM (接线图):



FLOW RATE CURVE (风量曲线):



UNIT 类型	Axial fan motor 外转子轴流风机
MOTOR 电机型式	Three phases motor
MOTOR TYPE 电机型号	YWF6D-800S-180/75-G
VOLTAGE 额定电压 (V)	400
FREQUENCY 频率 (Hz)	50
INPUT POWER 输入功率 (W)	△/Y 1200/930
CURRENT 电流 (A)	△/Y 2.85/1.65
SPEED 转速 (r/min)	△/Y 920/770
AIR FLOW 风量 20Pa(m³/h)	△/Y 19860/16590
NOISE 噪音 (dBA)	△/Y 75/74
ROTATION 旋转方向	CW ,looking into the end-shield 顺时针, 从端盖端方向看
INSULATION CLASS 绝缘等级	F
MOTOR PROTECTION 电机保护	Thermocontact 150±5℃ 热保护器
TEMPERATURE RISE 温升	75K max 运行温升不超过75K
PROTECTION CLASS 防护等级	IP54
OPERATING TYPE 工作定额	S1 连续工作制
AMBIENT TEMPERATURE 适用环境温度	-30℃ +60℃
BEARINGS 轴承型式	Ball bearings 滚珠轴承
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
ELECTRICAL CONNECTION 电源线	Lead wire 1330UL 7G 1.31mm²+ 2G 0.35mm², Length 100mm in terminal box connected 接线盒 (7芯1.31mm²+2芯0.35mm²线长100mm)
APPROVALS 认证标记	CCC、CE
NET WEIGHT/GROSS WEIGHT净重/毛重	35/50kg
PACKING 包装	89*89*27.5cm

								SIGN		DATE	TITLE YWF6D-800S-180/75-G
								DRN.BY			
								CHD.BY			
								ENG.BY			
								APP.BY			PROJECTION
REV.	DESCRIPTION	APPROVED	DATE								A4 SCALE SHEET: of