



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydraulic Oil HLP ZF

AIMOL Hydraulic Oil HLP ZF -



2-4



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydraulic Oil HLP ZF

AIMOL Hydraulic Oil HLP ZF -

- ◆ DIN 51524 2 (HLP)
- ◆ Denison HF-0/HF-1/HF-2
- ◆ Eaton M-2950-S
- ◆ Cincinnati Milacron P68/P69/P70
- ◆ ISO 11158
- ◆ ASTM D6158
- ◆ SAE MS 1004
- ◆ Bosch Rexroth RE 90220
- ◆ GM LS-2
- ◆ Conestoga pump test ISO 20763

		HLP ZF 32	HLP ZF 46	HLP ZF 68
20° C, /	ASTM D1298	0.870	0.874	0.880
, °C	ASTM D97	210	212	215
-20° C,	ASTM D4052	2506.9	-	-
0° C,	ASTM D4052	350.3	597.0	1093.3
40° C,	ASTM D445	32	46	68
100° C,	ASTM D445	5.38	6.7	8.6
	ASTM D2270	100	100	95
° C	ASTM D97	-30	-24	-22
ASTM D943,	ASTM D943	3500	3500	3500
FZG	FZG A/8.3/90	11	12	12
	ISO 4406	20/18/14		
, %	-	0	0	0

AIMOL Hydraulic Oil HLP ZF -

AIMOL

AIM b.v.