



C0059E | HYPERCELL

HPL N female connector

GENERAL CHARACTERISTICS

Inner Conductor:	Silver - plated bronze
Dielectric:	PTFE
Body:	Copper alloy - plated brass
Clamping and Coupling Nut:	Nickel - plated brass
Clamping Nut Waterproof:	Silicone O-ring

MECHANICAL & ENVIRONMENTAL

Interface Durability:	500 cycles	
Temperature:	Operating	-40°C / +85°C
	Storage	-40°C / +85°C
Weight:	85 g	
Waterproof Index:	IP68	
RoHS Compliance:	Yes	

ELECTRICAL

Impedance:	50 ± 1 Ω
Operating Frequency Band:	DC ~ 3GHz
VSWR (0 ~ 3 GHz):	≤ 1.10
3rd Order Passive Intermodulation, Measured In Swept Frequency Mode with 2 20W carriers, F ≤ 1880 MHz:	≤ -145 dBc
Voltage Test (at sea level):	2500 V eff / 50 Hz
Operating Voltage (at sea level):	1600 V eff / 50 Hz

Insulation Resistance:	$\geq 5000 \text{ M}\Omega$
Contact Resistance:	Inner contact: $\leq 1.5 \text{ m}\Omega$
	Outer contact: $\leq 1.0 \text{ m}\Omega$

RANGE

Compatibility with ACOME HPL 50 -1/2F

M1473, M2831, M5453, M5398

Test Methods: IEC 61169, IEC 62037, IEC 60529

NORMS AND STANDARDS

RECOMMENDATIONS

INSTALLATION INSTRUCTION

ANM - C0059X